

Note Language: English**Version:** 3 **Validity:** Valid Since 26.07.2012

Summary

Symptom

Many customers have questions of how to enable/disable HANA for BPC

Other terms

BPC on HANA

Reason and Prerequisites

Consulting

Solution

Enable/Disable HANA for BPC is controlled by two parameters from HANA SP01:

- o `ENABLE_ACCELERATOR`

This global IMG parameter is to control whether HANA can be enabled or not in BPC system level. Y or X is to enable, empty value is to disable.

- o `ACCELERATOR_ON`

This environment IMG parameter is to control whether HANA can be enabled or not in environment level. Y or X is to enable, empty value is to disable. An environment becomes HANA enable only if both `ENABLE_ACCELERATOR` and `ACCELERATOR_ON` are set to Y or X.

Run program `BPC_HANA_MIGRATE_FROM_10` for the environments that are created before enabling HANA.

Header Data

Release Status:	Released for Customer
Released on:	26.07.2012 08:11:11
Master Language:	English
Priority:	Correction with high priority
Category:	Consulting
Primary Component:	EPM-BPC-NW NetWeaver Version

Valid Releases

Software Component	Release	From Release	To Release	and Subsequent
HANABPC	800	800	800	

Related Notes

Number	Short Text
1734706	BPC 10.0 NW on HANA (HANABPC) Collective Note